



CD40192

4-bit up/down BCD counter

Product Specification

Specification Revision History:

Version	Date	Description
2023-04-A1	2023-04	New



Contents

1、General Description.....	3
2、Block Diagram And Pin Description	4
2.1、Block Diagram	4
2.2、Pin Configurations.....	4
2.3、Pin Description.....	5
2.4、Function Table.....	5
3、Electrical Parameter	5
3.1、Absolute Maximum Ratings.....	5
3.2、Recommended Operating Conditions	6
3.3、Electrical Characteristics.....	6
3.3.1、DC Characteristics 1	6
3.3.2、DC Characteristics 2.....	7
3.3.3、AC Characteristics 1.....	7
3.3.4、AC Characteristics 2.....	9
4、Testing Circuit	11
4.1、AC Testing Circuit	11
4.2、Test Data	11
4.3、AC Testing Waveforms.....	11
4.4、Measurement Points	12
5、Package Information.....	13
5.1、DIP16	13
5.2、SOP16	14
5.3、TSSOP16.....	15
6、Statements And Notes	16
6.1、The name and content of Hazardous substances or Elements in the product.....	16
6.2、Notes	16



1、General Description

The CD40192 is a 4-bit synchronous up/down BCD counter.

Features:

- Supply voltage range: 3V to 15V
- Temperature range: -40°C to +125°C
- Packaging information: DIP16/SOP16/TSSOP16

Ordering Information:

Tube packing specifications:

Part number	Packaging form	Marking code	Tube quantity	Boxed tube quantity	Boxed quantity	Notes
CD40192DA16.TB	DIP16	CD40192	25 PCS/tube	40 tube/box	1000 PCS/box	Dimensions of plastic enclosure: 19.0mm×6.4mm Pin spacing: 2.54mm
CD40192SA16.TB	SOP16	CD40192	50 PCS/tube	200 tube/box	10000 PCS/box	Dimensions of plastic enclosure: 10.0mm×3.9mm Pin spacing: 1.27mm
CD40192TA16.TB	TSSOP16	CD40192	96 PCS/tube	200 tube/box	19200 PCS/box	Dimensions of plastic enclosure: 5.0mm×4.4mm Pin spacing: 0.65mm

Reel packing specifications:

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
CD40192SA16.TR	SOP16	CD40192	4000PCS/reel	8000PCS/box	Dimensions of plastic enclosure: 10.0mm×3.9mm Pin spacing: 1.27mm
CD40192TA16.TR	TSSOP16	CD40192	5000PCS/reel	10000PCS/box	Dimensions of plastic enclosure: 5.0mm×4.4mm Pin spacing: 0.65mm

Note: If the physical information is inconsistent with the ordering information, please refer to the actual product.



2、Block Diagram And Pin Description

2.1、Block Diagram





Figure 1. Functional diagram

2.2、Pin Configurations





2.3、Pin Description

Pin No.	Pin Name	Description
1	D1	parallel data input
2	Q1	buffered counter output
3	Q0	buffered counter output
4	CPD	count-down clock pulse input (LOW-to-HIGH, edge-triggered)
5	CPU	count-up clock pulse input (LOW-to-HIGH, edge-triggered)
6	Q2	buffered counter output
7	Q3	buffered counter output
8	V _{SS}	ground supply voltage
9	D3	parallel data input
10	D2	parallel data input
11	$\overline{\text{PL}}$	parallel load input (active low)
12	$\overline{\text{TCU}}$	buffered terminal count-up (carry) output (active LOW)
13	$\overline{\text{TCD}}$	buffered terminal count-down (borrow) output (active LOW)
14	MR	master reset input (asynchronous)
15	D0	parallel data input
16	V _{DD}	supply voltage

2.4、Function Table

MR	$\overline{\text{PL}}$	CPU	CPD	Mode
H	X	X	X	reset(asynchronous)
L	L	X	X	parallel load
L	H	↑	H	count-up
L	H	H	↑	count-down

Note: H=HIGH voltage level; L=LOW voltage level. X=don't care;↑=positive-going transition;

3、Electrical Parameter

3.1、Absolute Maximum Ratings

(Voltages are referenced to V_{SS} (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V _{DD}	-	-0.5	+18	V
input voltage	V _I	all inputs	-0.5	V _{DD} +0.5	V
DC input current	I _{IK}	any one input	-	±10	mA
storage temperature	T _{stg}	-	-65	+150	°C
soldering temperature	T _L	10s	DIP	245	°C
			SOP/TSSOP	260	



3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{DD}	-	3	-	15	V
ambient temperature	T_{amb}	in free air	-40	-	+125	°C

3.3、Electrical Characteristics

3.3.1、DC Characteristics 1

($T_{amb}=-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to V_{SS} (ground=0V), unless otherwise specified.)

Parameter	Symbol	V_{DD}	Conditions	Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	5V	-	3.5	-	-	V
		10V	-	7	-	-	V
		15V	-	11	-	-	V
LOW-level input voltage	V_{IL}	5V	-	-	-	1.5	V
		10V	-	-	-	3	V
		15V	-	-	-	4	V
HIGH-level output voltage	V_{OH}	5V	$ I_O <1\mu\text{A}$	4.95	-	-	V
		10V	$ I_O <1\mu\text{A}$	9.95	-	-	V
		15V	$ I_O <1\mu\text{A}$	14.95	-	-	V
LOW-level output voltage	V_{OL}	5V	$ I_O <1\mu\text{A}$	-	-	0.05	V
		10V	$ I_O <1\mu\text{A}$	-	-	0.05	V
		15V	$ I_O <1\mu\text{A}$	-	-	0.05	V
HIGH-level output current	I_{OH}	5V	$V_O=4.6\text{V}$	-	-	-0.34	mA
		5V	$V_O=2.5\text{V}$	-	-	-1.3	mA
		10V	$V_O=9.5\text{V}$	-	-	-0.55	mA
		15V	$V_O=13.5\text{V}$	-	-	-1.65	mA
LOW-level output current	I_{OL}	5V	$V_O=0.4\text{V}$	0.34	-	-	mA
		10V	$V_O=0.5\text{V}$	0.46	-	-	mA
		15V	$V_O=1.5\text{V}$	1.4	-	-	mA
input leakage current	I_I	15V	$V_I=15\text{V}$ or GND	-	-	± 2	μA
supply current	I_{DD}	5V	$V_I=5\text{V}$ or GND; $I_O=0\text{A}$	-	-	7.5	μA
		10V	$V_I=10\text{V}$ or GND; $I_O=0\text{A}$	-	-	15	μA
		15V	$V_I=15\text{V}$ or GND; $I_O=0\text{A}$	-	-	30	μA

**3.3.2、DC Characteristics 2**(T_{amb}=-40°C to +125°C, voltages are referenced to V_{SS} (ground=0V), unless otherwise specified.)

Parameter	Symbol	V _{DD}	Conditions	Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	5V	-	3.5	-	-	V
		10V	-	7	-	-	V
		15V	-	11	-	-	V
LOW-level input voltage	V _{IL}	5V	-	-	-	1.5	V
		10V	-	-	-	3	V
		15V	-	-	-	4	V
HIGH-level output voltage	V _{OH}	5V	I _O <1uA	4.95	-	-	V
		10V	I _O <1uA	9.95	-	-	V
		15V	I _O <1uA	14.95	-	-	V
LOW-level output voltage	V _{OL}	5V	I _O <1uA	-	-	0.05	V
		10V	I _O <1uA	-	-	0.05	V
		15V	I _O <1uA	-	-	0.05	V
HIGH-level output current	I _{OH}	5V	V _O =4.6V	-	-	-0.3	mA
		5V	V _O =2.5V	-	-	-1.15	mA
		10V	V _O =9.5V	-	-	-0.45	mA
		15V	V _O =13.5V	-	-	-1.4	mA
LOW-level output current	I _{OL}	5V	V _O =0.4V	0.29	-	-	mA
		10V	V _O =0.5V	0.38	-	-	mA
		15V	V _O =1.5V	1.2	-	-	mA
input leakage current	I _I	15V	V _I =15V or GND	-	-	±4	uA
supply current	I _{DD}	5V	V _I =5V or GND; I _O =0A	-	-	7.5	uA
		10V	V _I =10V or GND; I _O =0A	-	-	15	uA
		15V	V _I =15V or GND; I _O =0A	-	-	30	uA

3.3.3、AC Characteristics 1(T_{amb}=-40°C to +85°C, V_{SS}=0V, unless otherwise specified.)

Parameter	Symbol	V _{DD}	Conditions	Min.	Typ.	Max.	Unit
HIGH to LOW propagation delay time	t _{PHL}	5V	CPU to Qn See Figure 4	-	210	415	ns
		10V		-	85	165	ns
		15V		-	60	120	ns
		5V	CPD to Qn See Figure 4	-	210	425	ns
		10V		-	85	170	ns
		15V		-	60	125	ns
		5V	CPU to $\overline{T\text{CU}}$	-	125	250	ns
		10V		-	50	100	ns
		15V		-	35	70	ns
		5V	CPD to $\overline{T\text{CD}}$	-	140	280	ns
		10V		-	55	110	ns
		15V		-	40	80	ns
		5V	MR to Qn	-	195	390	ns
		10V		-	80	160	ns



		15V	MR to $\overline{TCD}$	-	60	120	ns
		5V		-	365	730	ns
		10V		-	130	265	ns
		15V		-	100	205	ns
		5V	$\overline{PL}$ to Qn	-	185	360	ns
		10V		-	75	150	ns
		15V		-	55	110	ns
LOW to HIGH propagation delay time	t_{PLH}	5V	CPU to Qn See Figure 4	-	170	340	ns
		10V		-	70	140	ns
		15V		-	50	100	ns
		5V	CPD to Qn See Figure 5	-	170	340	ns
		10V		-	70	140	ns
		15V		-	50	100	ns
		5V	CPU to $\overline{TCD}$	-	95	185	ns
		10V		-	40	80	ns
		15V		-	30	60	ns
		5V	CPD to $\overline{TCD}$	-	100	195	ns
		10V		-	40	85	ns
		15V		-	30	65	ns
		5V	MR to $\overline{TCD}$	-	145	285	ns
		10V		-	60	115	ns
		15V		-	45	90	ns
		5V	$\overline{PL}$ to Qn	-	145	290	ns
		10V		-	60	120	ns
		15V		-	45	90	ns
transition time	t_{THL}, t_{TLH}	5V	See Figure 4	-	60	120	ns
		10V		-	30	60	ns
		15V		-	20	40	ns
set-up time	t_{su}	5V	Dn to $\overline{PL}$	160	80	-	ns
		10V		60	30	-	ns
		15V		50	25	-	ns
hold time	t_{hold}	5V	Dn to $\overline{PL}$	+10	-70	-	ns
		10V		+5	-25	-	ns
		15V		+5	-20	-	ns
pulse width	t_w	5V	CPU or CPD LOW; minimum width	150	75	-	ns
		10V		50	25	-	ns
		15V		35	20	-	ns
		5V	MR input HIGH minimum width	180	90	-	ns
		10V		70	35	-	ns
		15V		60	30	-	ns
		5V	$\overline{PL}$ input LOW minimum width	120	60	-	ns
		10V		45	20	-	ns
		15V		30	15	-	ns
recovery time	t_{rec}	5V	MR input	125	65	-	ns
		10V		70	35	-	ns



		15V	$\overline{PL}$ input	50	25	-	ns
		5V		90	45	-	ns
		10V		35	15	-	ns
		15V		25	10	-	ns
maximum clock pulse frequency	fmax	5V	-	2.5	5	-	MHZ
		10V	-	7	14	-	MHZ
		15V	-	9	18	-	MHZ

3.3.4、AC Characteristics 2

(T_{amb}=-40°C to +125°C, V_{SS}=0V, unless otherwise specified.)

Parameter	Symbol	V _{DD}	Conditions	Min.	Typ.	Max.	Unit
HIGH to LOW propagation delay time	t _{PHL}	5V	CPU to Qn See Figure 4	-	-	498	ns
		10V		-	-	198	ns
		15V		-	-	144	ns
		5V	CPD to Qn See Figure 4	-	-	510	ns
		10V		-	-	204	ns
		15V		-	-	150	ns
		5V	CPU to $\overline{T\ CU}$	-	-	300	ns
		10V		-	-	120	ns
		15V		-	-	84	ns
		5V	CPD to $\overline{T\ CD}$	-	-	336	ns
		10V		-	-	132	ns
		15V		-	-	96	ns
		5V	MR to Qn	-	-	468	ns
		10V		-	-	192	ns
		15V		-	-	144	ns
		5V	MR to $\overline{T\ CD}$	-	-	876	ns
		10V		-	-	318	ns
		15V		-	-	246	ns
LOW to HIGH propagation delay time	t _{PLH}	5V	CPU to Qn See Figure 4	-	-	432	ns
		10V		-	-	180	ns
		15V		-	-	132	ns
		5V	CPD to Qn See Figure 5	-	-	408	ns
		10V		-	-	168	ns
		15V		-	-	120	ns
		5V	CPU to $\overline{T\ CU}$	-	-	222	ns
		10V		-	-	96	ns
		15V		-	-	72	ns
		5V	CPD to $\overline{T\ CD}$	-	-	234	ns
		10V		-	-	102	ns
		15V		-	-	78	ns
		5V	MR to $\overline{T\ CU}$	-	-	342	ns



		10V	$\overline{PL}$ to Qn	-	-	138	ns
		15V		-	-	108	ns
		5V		-	-	348	ns
		10V		-	-	144	ns
		15V		-	-	108	ns
transition time	t_{THL}, t_{TLH}	5V	See Figure 4	-	-	144	ns
		10V		-	-	72	ns
		15V		-	-	48	ns
set-up time	t_{su}	5V	Dn to $\overline{PL}$	192	-	-	ns
		10V		72	-	-	ns
		15V		60	-	-	ns
hold time	t_{hold}	5V	Dn to $\overline{PL}$	+12	-	-	ns
		10V		+6	-	-	ns
		15V		+6	-	-	ns
pulse width	t_w	5V	CPU or CPD LOW; minimum width	180	-	-	ns
		10V		60	-	-	ns
		15V		42	-	-	ns
		5V	MR input HIGH minimum width	216	-	-	ns
		10V		84	-	-	ns
		15V		72	-	-	ns
		5V	$\overline{PL}$ input LOW minimum width	144	-	-	ns
		10V		54	-	-	ns
		15V		36	-	-	ns
recovery time	t_{rec}	5V	MR input	150	-	-	ns
		10V		84	-	-	ns
		15V		60	-	-	ns
		5V	$\overline{PL}$ input	108	-	-	ns
		10V		42	-	-	ns
		15V		30	-	-	ns
maximum clock pulse frequency	f_{max}	5V	-	2	-	-	MHZ
		10V	-	6	-	-	MHZ
		15V	-	7.5	-	-	MHZ



4、Testing Circuit

4.1、AC Testing Circuit




Figure 3. Load circuit

C_L includes probe and jig capacitance.

4.2、Test Data

Supply voltage	Input		Load	V_{EXT}		
V_{DD}	V_I	$t_r = t_f$	C_L	t_{PLH}/t_{PHL}	t_{PLZ}/t_{PZL}	t_{PHZ}/t_{PZH}
5V to 15V	V_{DD}	$\leq 20\text{ns}$	50pF	Open	V_{DD}	V_{SS}

4.3、AC Testing Waveforms




Figure 4. Propagation delay, output transition time




Figure 5. Minimum pulse widths for CP and MR, MR to CP recovery time, and set-up and hold time for Dn to CP


4.4、 Measurement Points

Supply voltage	Input	Output		
V_{DD}	V_M	V_M	V_X	V_Y
5V to 15V	$0.5 \times V_{DD}$	$0.5 \times V_{DD}$	$0.1 \times V_{DD}$	$0.9 \times V_{DD}$



5、Package Information




5.1、DIP16



Symbol	Dimensions (mm)	
	Min.	Max.
A2	3.20	3.60
A1	0.51	-
A	3.60	5.33
L	3.00	3.60
b	0.36	0.56
B1	1.52	
D	18.80	19.94
E1	6.20	6.60
e	2.54	
c	0.20	0.36
eB	7.62	9.30






5.2、SOP16



Symbol	Dimensions (mm)	
	Min.	Max.
A	1.35	1.80
A1	0.10	0.25
A2	1.25	1.55
b	0.33	0.51
c	0.19	0.25
D	9.50	10.10
E	5.80	6.30
E1	3.70	4.10
e	1.27	
L	0.35	0.89
θ	0°	8°



5.3、TSSOP16



Symbol	Dimensions (mm)	
	Min.	Max.
A	-	1.20
A1	0.05	0.15
A2	0.80	1.05
b	0.19	0.30
c	0.09	0.20
D	4.90	5.10
E1	4.30	4.50
E	6.20	6.60
e	0.65	
L	0.45	0.75
θ	0°	8°



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We Recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials from i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.